



SAFETY DATA SHEET

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

Product number 205/WB101/T - BASE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses BASE FOR TWO COMPONENT ANTI-GRAFFITI COATING

Uses advised against NOT SUITABLE FOR USE IN HOMEWOKER (DIY) APPLICATIONS

1.3. Details of the supplier of the safety data sheet

Supplier

COO-VAR
Lockwood Street
Hull
HU2 0HN
+44 (0) 1482 328053(T)
+44 (0) 1482 219266(F)
info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) R43. R10,R52/53.

Human health See Section 11 for additional information on health hazards. The product contains a sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.

2.2. Label elements

Pictogram



Signal word

Warning

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

Hazard statements	H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P501 Dispose of contents/ container to ...
Contains	WATER THINNABLE POLYACRYLATE CONTAINING HYDROXYL GROUPS
Supplementary precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground/ bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P272 Contaminated work clothing should not be allowed out of the workplace. P302+P352 IF ON SKIN: Wash with plenty of water. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P363 Wash contaminated clothing before reuse. P403+P235 Store in a well-ventilated place. Keep cool. P321 Specific treatment (see medical advice on this label). P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P261 Avoid breathing vapour/ spray.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

WATER THINNABLE POLYACRYLATE CONTAINING HYDROXYL GROUPS	30-60%
CAS number: —	
Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Sens. 1 - H317	R43.
2-BUTOXYETHANOL	1-5%
CAS number: 111-76-2	EC number: 203-905-0
Classification	Classification (67/548/EEC or 1999/45/EC)
Acute Tox. 4 - H302	Xn;R20/21/22 Xi;R36/38
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

SOLVENT NAPHTHA, LIGHT AROMATIC(content of benzene <0.1%)		1-5%
CAS number: 64742-95-6	EC number: 265-199-0	REACH registration number: 01-2119455851-35
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.	
2-DIMETHYLAMINOETHANOL		1-5%
CAS number: 108-01-0	EC number: 203-542-8	REACH registration number: 01-2119492298-24-0000
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335	R10 C;R34 Xn;R20/21/22	
ACETONE		<1%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-0000
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	F;R11 Xi;R36 R66 R67	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

4.2. Most important symptoms and effects, both acute and delayed

General information Get medical attention promptly if symptoms occur after washing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours. FLAMMABLE. Solvent vapours may form explosive mixtures with air.

5.3. Advice for firefighters

Protective actions during firefighting Risk of re-ignition after fire has been extinguished. Cool containers exposed to flames with water until well after the fire is out. Avoid the spillage or runoff entering drains, sewers or watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

Usage precautions Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalies. Acids.
Storage class	Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resistant cupboard or bin. Larger quantities must be kept in a separate , marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
Usage description	Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³

Sk

Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³

SOLVENT NAPHTHA, LIGHT AROMATIC(content of benzene <0.1%)

Long-term exposure limit (8-hour TWA): SUP 600 mg/m³

2-DIMETHYLAMINOETHANOL

Long-term exposure limit (8-hour TWA): WEL 2 ppm 7.4 mg/m³

Short-term exposure limit (15-minute): WEL 6 ppm 22 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through skin.

SOLVENT NAPHTHA, LIGHT AROMATIC(content of benzene <0.1%) (CAS: 64742-95-6)

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

DNEL

Industry - Dermal; Long term systemic effects: 25 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 150 mg/m³
 Consumer - Inhalation; Long term systemic effects: 32 mg/m³
 Consumer - Oral; Long term systemic effects: 11 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 11 mg/kg/day

8.2. Exposure controls

Protective equipment**Appropriate engineering controls**

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Creamy liquid.

Colour Milky.

Odour Slight.

pH pH (concentrated solution): Alkaline

Initial boiling point and range approx. 100°C @

Flash point 45°C CC (Closed cup).

Upper/lower flammability or explosive limits : Solvent naphtha 1.0% by vol., 2-butoxyethanol 1.1% by vol.

Vapour density heavier than air

Relative density approx. 1.08 g/ml @ 20°C

Solubility(ies) Miscible with water

Viscosity approx. 800 DIN 53019/1 mPas @ 23°C

9.2. Other information

Volatility 55% by weight

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

Volatile organic compound This product contains a maximum VOC content of 83 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The material shows a sensitizing effect in conjunction with some complex hydrocarbons such as the Solvent Naphthas through skin absorption, and is considered to be an inherent property of the mixture.

Inhalation Vapour from this product may be hazardous by inhalation. Vapour may irritate respiratory system/lungs.

Ingestion Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

Skin contact Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema. Prolonged or repeated exposure may cause severe irritation. May cause sensitisation by skin contact.

Eye contact May cause temporary eye irritation.

Acute and chronic health hazards May cause sensitisation by skin contact.

Route of entry Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

Medical considerations Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration.

Toxicological information

WATER THINNABLE POLYACRYLATE CONTAINING HYDROXYL GROUPS

Toxicological effects Salmonella/microsome test (Ames test). No indication of mutagenic effects.

Skin sensitisation

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

Skin sensitisation Local Lymph Node Assay (LLNA) - Rat: Epidemiological studies have shown evidence of skin sensitisation. The material shows a sensitizing effect in conjunction with some complex hydrocarbons such as the Solvent Naphthas through skin absorption, and is considered to be an inherent property of the mixture.

Germ cell mutagenicity

Genotoxicity - in vitro Ames test: Negative. This substance has no evidence of mutagenic properties.

2-BUTOXYETHANOL

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀) 435.0 mg/kg

Species Rabbit

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Moderately irritating.

Germ cell mutagenicity

Genotoxicity - in vitro This substance has no evidence of mutagenic properties.

Reproductive toxicity

Reproductive toxicity - fertility Fertility - NOAEL 720 mg/kg, Oral, Mouse F1 Fertility - NOAEL 720 mg/kg, Oral, Mouse F2a Fertility - NOAEL 720 mg/kg, Oral, Mouse P

Skin contact May be absorbed through the skin.

SOLVENT NAPHTHA, LIGHT AROMATIC(content of benzene <0.1%)

Acute toxicity - oral

Acute toxicity oral (LD₅₀) 3,592.0 mg/kg

Species Rat

ATE oral (mg/kg) 3,592.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀) 3,160.0 mg/kg

Species Rabbit

ATE dermal (mg/kg) 3,160.0

Acute toxicity - inhalation

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

Acute toxicity inhalation (LC₅₀ vapours mg/l)	6,193.0
Species	Rat
ATE inhalation (vapours mg/l)	6,193.0
Skin corrosion/irritation	
Animal data	Slightly irritating.
Inhalation	Irritating to respiratory system. Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.
Ingestion	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
Skin contact	Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological Information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

SOLVENT NAPHTHA, LIGHT AROMATIC(content of benzene <0.1%)

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

2-BUTOXYETHANOL

Acute toxicity - fish	NOEC, : >100 mg/l, Algae
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 70.7 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 1840 mg/l, Scenedesmus subspicatus

SOLVENT NAPHTHA, LIGHT AROMATIC(content of benzene <0.1%)

Acute toxicity - fish	LC ₅₀ , ~ 96 hours: 9.22 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , ~ 48 hours: 6.14 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , ~ 96 hours: 19 mg/l, Freshwater algae
Acute toxicity - microorganisms	EC ₅₀ , : 1 - 10 mg/l,

12.2. Persistence and degradability

Persistence and degradability The product is slowly degradable.

2-BUTOXYETHANOL

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

Persistence and degradability The product is expected to be biodegradable.

Biodegradation - 90 Degradation (%):

Biological oxygen demand ~ 0.756 g O₂/g substance

Chemical oxygen demand ~ 2.379 g O₂/g substance

SOLVENT NAPHTHA, LIGHT AROMATIC(content of benzene <0.1%)

Persistence and degradability The product is readily biodegradable.

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Avoid the spillage or runoff entering drains, sewers or watercourses.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDG CPL2, ADR and IMDG.

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) Resin solution

Proper shipping name (IMDG) Resin solution

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

Proper shipping name (ICAO) Resin solution

Proper shipping name (ADN) Resin solution

14.3. Transport hazard class(es)

ADR/RID class 1263

IMDG class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

14.6. Special precautions for user

EmS F-E, S-E

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Workplace Exposure Limits EH40.
CHIP for everyone HSG228.
Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.
Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Only trained personnel should use this material.

205/WB101 - 2 PACK ANTI-GRAFFITI COATING - CLEAR BASE

Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Update for CLP labelling.
Issued by	Technical Dept. (P.E.)
Revision date	27/05/2015
Revision	5
Supersedes date	14/01/2013
SDS number	10754
SDS status	Approved.
Signature	Initials _____
Risk phrases in full	<p>R10 Flammable. R20/21/22 Harmful by inhalation, in contact with skin and if swallowed. R34 Causes burns. R36/38 Irritating to eyes and skin. R37 Irritating to respiratory system. R43 May cause sensitisation by skin contact. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.</p>
Hazard statements in full	<p>EUH066 Repeated exposure may cause skin dryness or cracking. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.