



FLOOR PRIMER ES40

A high performance two pack water based floor primer for power floated concrete & other absorbent smooth floor surfaces

Recommended Areas of Use

Interior smooth absorbent floor substrates, especially power floated concrete & quarry tiles, which may require a penetrating primer to improve the adhesion of subsequent Bradite floor coatings. Note, this product is free from APEOs and benzyl alcohol.

Certificates & Approvals

Manufactured under the auspices of an ISO 9001:2008 quality & ISO 14001:2004 environmental management systems.

2004/42/EC EU limit value for this product (cat.A/h wb): 30g/l (2010). This product contains max.2 g/l VOC.

Properties

| | | | |
|---------------------------------------|-------------------------------------|---------------------------------------|--|
| Gloss | Not applicable, absorbed by surface | Surface dry | 1 hour |
| Theoretical Coverage | 25 m ² /L/coat | Minimum over coating time | 2.5 hours minimum |
| Recommended number of coats | 1 coat | Maximum over coating time | Unlimited (after preparation) |
| Density | 1.18 kg/L (base, as supplied) | Minimum application conditions | Temperature > 10°C, RH < 65% (but must be 3 °C above dew point) |
| Volume solids | 47% (mixed, after thinning) | Time to light traffic | 2 hours minimum |
| Flash point (Abel closed cup) | >99°C | Full cure | 5 days |
| VOC | <2 g/L | Shelf life | 12 months minimum in original unopened containers. |
| Thinner / Cleaning | Water | Colour range | Clear only |
| Pot Life | 1 hour | Mix Ratio | Base & Activator tins are supplied pre-measured. Clean cold tap water is used for third component (see mixing instructions for details). For part mixing use: 2.5: 1.5: 1.0 (v/v) or 100: 63: 38 pbw |
| Recommended wet film thickness | 40 microns/coat | Recommended dry film thickness | Not measureable since absorbed by substrate. |

Suitable Surfaces

For concrete and other absorbent mineral substrates which are dry, free of contamination, dust and efflorescence. [Note, not suitable for applying over existing floor paint systems].

Application Information

Material must be thinned (see specific mixing information below) prior to application on new or uncoated concrete to enable penetration and binding of substrate. Application and use should always conform to the codes of practice described in BS 6150 and BS 5493.

Brush and Roller – On smooth substrates, the use of a suitably sized foam or short pile roller is highly recommended.

Conventional Air & Airless Spraying – Not recommended

Cleaning

Clean all equipment immediately after use with clean tap water for best results.

Specification

Consult specific product datasheet for subsequent Bradite floor coating finish for additional information.

Floor Preparation:

New concrete should be allowed to dry for at least 28 days prior to painting. Moisture content of floor may be checked by placing a secured sheet of plastic on the floor for 24 hours and then examining for any signs of condensation. Appearance of condensation indicates concrete is not sufficiently dry to allow painting.

Existing coatings must be completely removed. For best performance, complete vacuum blast cleaning of the substrate is recommended. Bradite TD39 industrial strength detergent washing and rinsing should be used with scrubbing, if necessary, to remove grease or oil.

Mixing Instructions

- Pour complete contents of activator can into the base can.
- Mix thoroughly to an even cream colour and consistency (Use a cordless power drill, with paint paddle attachment, for best results).
- With mixing, add 1000ml of clean tap water.

Painting System

1st coat Bradite Floor Primer ES40

Subsequent coats will be dependent upon the desired Bradite floor coating system. Bradite Floor Primer may be slightly tacky underfoot when applying finishing system. Please consult specific floor finishing product datasheet for further system details. The end user and applicator must ensure that the finished floor is safe against slips in all likely usage conditions.

Summary Safety Information

Always refer to the Health and Safety sheet for the product before use and observe the warning phrases on the label.

Disclaimer - The information on this data sheet is correct to the best of our knowledge and experience. Bradite reserves the right to modify data contained herein, without notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service and application may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FLOOR PRIMER

Product code: ES40

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: Bradite Paints
Ogwen Valley Works
Bethesda
Gwynedd
LL57 4YP
United Kingdom

Tel: +44 (0)1248 600315

Fax: +44 (0)1248 602782

Email: sales@bradite.com

1.4. Emergency telephone number

Emergency tel: +44 (0)1248 600315
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion
GHS07: Exclamation mark



SAFETY DATA SHEET

FLOOR PRIMER

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor.

P321: Specific treatment (see instructions on this label).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

FORMALDEHYDE, POLYMER WITH N1-(2-AMINOETHYL)-N2-[2-AMINOETHYL]AMINO]ETHYL]-1,2-ETHANEDIAMINE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLE)

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|--------|-------------|-----------|---|---------|
| - | 180583-06-6 | - | Skin Sens. 1: H317; Aquatic Chronic 2: H411 | 10-30% |

O,O'-BIS(2-AMINOPROPYL)POLYPROPYLENEGLYCOL

| | | | | |
|-----------|-----------|---|--|-------|
| 618-561-0 | 9046-10-0 | - | Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Corr. 1C: H314 | 1-10% |
|-----------|-----------|---|--|-------|

3,6,9-TRIAZAUNDECAMETHYLENEDIAMINE

| | | | | |
|-----------|----------|---|--|-------|
| 203-986-2 | 112-57-2 | - | Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 2: H411 | 1-10% |
|-----------|----------|---|--|-------|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be soreness and redness of the mouth and throat.

[cont...]

SAFETY DATA SHEET

FLOOR PRIMER

Page: 3

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the spillage site with large amounts of water.
Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

Storage quantity limits: N/A

7.3. Specific end use(s)

Specific end use(s): PC9a: Coatings and paints, thinners, paint removers.

[cont...]

SAFETY DATA SHEET

FLOOR PRIMER

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Characteristic odour

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible in all proportions

Also soluble in: Ethanol.

Viscosity: Non-viscous

Boiling point/range°C: 100

Melting point/range°C: Not applicable.

Flammability limits %: lower: Not applicable.

upper: Not applicable.

Flash point°C: >93

Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable.

Vapour pressure: Not applicable.

Relative density: 1.05

pH: 8.5

VOC g/l: <1

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET

FLOOR PRIMER

Page: 5

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

3,6,9-TRIAZAUNDECAMETHYLENEDIAMINE

| | | | | |
|-----|-----|------|------|-------|
| IPR | RAT | LD50 | 205 | mg/kg |
| IVN | MUS | LD50 | 320 | mg/kg |
| ORL | RAT | LD50 | 3990 | mg/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|--------------------------------|-------|-----------------------|
| Skin corrosion/irritation | DRM | Hazardous: calculated |
| Serious eye damage/irritation | OPT | Hazardous: calculated |
| Respiratory/skin sensitisation | DRM | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

[cont...]

SAFETY DATA SHEET

FLOOR PRIMER

Page: 6

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Waste code number: 08 01 12

Disposal of packaging: Retain for recovery.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

[cont...]

SAFETY DATA SHEET

FLOOR PRIMER

Page: 7

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.